

ARCHETYPE



A
L
U
M
I
N
I
U
M



12x24




12x12

H
O
R
N



12x24



12x12

M
O
J
A
V
E



12x24



12x12

W
A
Y
N
E
S
B
O
R
O



12x24



12x12

	VALUE	STANDARD
Abrasion resistance	Beige PEI 4 Brown PEI 4 Grey PEI 4	GLAZED ISO 10545-7
Water absorption	0.20%	C373
Breaking strength	6x24: ≥3000 N 12x24: ≥1500 N	ISO 10545-4
Scratch hardness	7 Mohs	EN 101
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost thermal shock resistance	resistant- no alteration with 100 cycles	ISO 10545-12
Crazing resistance	resistant	ISO 10545-11
Color shade variation	V3	CTDA
Coefficients of friction	Wet: 0.60-0.65 Dry: 0.65-0.70	ISO 10545-17

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.


Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•



3x12 Floor Bullnose



Linear Mosaic



2x2 Basket Weave