

HAZAR



BEIGE



12x24 Jalousie (wall tile only)



6x36

GREY



12x24 Jalousie (wall tile only)



6x36


VALUE STANDARD

	VALUE	STANDARD
Abrasion resistance	Beige PEI 4 Grey PEI 4	GLAZED ISO 10545-7
Water absorption	6x36: Eb ≤% 0.3 12x24 Jalousie: ≥%12.5	ISO 10545-3
Breaking strength	6x36: ≥3000 N 12x24 Jalousie: ≥1100 N	ISO 10545-4
Scratch hardness	6x36: 9 Mohs 12x24 Jalousie: 5 Mohs	EN 101
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost	resistant- no alternation with 100 cycles	ISO 10545-12
Thermal shock resistance	resistant	ISO 10545-9
Crazing resistance	resistant	ISO 10545-11
Color shade variation	V2	CTDA
Coefficients of friction	6x36 only: Wet: 0.70	ANSI/NFSI B101.3-2012

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

6x36 only

Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•



2x2 Basket Weave