

SOHO



B
E
I
G
E



12x24

6x24

2x2 Basketweave, 3x12 Sbn (pattern against the grain) and 3x24 Sbn (pattern with the grain) also available

B
R
O
W
N



12x24

6x24

2x2 Basketweave, 3x12 Sbn (pattern against the grain) and 3x24 Sbn (pattern with the grain) also available

G
R
E
Y



12x24

6x24

2x2 Basketweave, 3x12 Sbn (pattern against the grain) and 3x24 Sbn (pattern with the grain) also available

	VALUE	STANDARD
Abrasion resistance	Beige PEI 4 Brown PEI 4 Grey PEI 4	GLAZED ISO 10545-7
Water absorption	E ≤ 0.3	ISO 10545-3
Breaking strength	6x24: ≥ 3000 N 12x24: ≥ 1500 N	ISO 10545-4
Scratch hardness	7 Mohs	EN 101
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost	resistant- no alternation with 100 cycles	ISO 10545-12
Thermal shock resistance	resistant	ISO 10545-9
Crazing resistance	resistant	ISO 10545-11
Color shade variation	V3	CIDA
Coefficients of friction	Wet: 0.60-0.65 Dry: 0.65-0.70	ISO 10545-17

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•



3x12 Floor Bullnose
(pattern against grain)



2x2 Basketweave
set on 13x13 mesh sheet



3x24 Floor Bullnose
(pattern with grain)



www.CosmosGranite.com