

VENUS



B
E
I
G
E



12x24



18x18



13x13



3x3 Mosaic

B
R
O
W
N



12x24



18x18



13x13



3x3 Mosaic


G
R
E
Y




12x24



18x18



13x13



3x3 Mosaic

I
V
O
R
Y



12x24



18x18



13x13



3x3 Mosaic


	VALUE	STANDARD
	Beige PEI 4 Grey PEI 4 Ivory PEI 4 Brown PEI 3	
Abrasion resistance		GLAZED ISO 10545-7
Water absorption	E ≤% 0.3	ISO 10545-3
Breaking strength	12x24: ≥1500 N 13x13: ≥ 1300 18x18: ≥ 1500	ISO 10545-4
Scratch hardness	8 Mohs	EN 101
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost	resistant- no alternation with 100 cycles	ISO 10545-12
Thermal shock resistance	resistant	ISO 10545-9
Crazing resistance	resistant	ISO 10545-11
Color shade variation	V3	CTDA
Coefficients of friction	Wet: 0.60-0.65 Dry: 0.65-0.70	ASTM C 1028 96

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•



3x13 Floor Bullnose
available for all colors



2x2 Basket Weave