

# BARBADOS



## EARTH



6x36

## SAND



6x36

## WHITE




6x36

	VALUE	STANDARD
	Earth PEI 3 Sand PEI 3 White PEI 4	
Abrasion resistance		GLAZED ISO 10545-7
Water absorption	Eb ≤% 0.3	ISO 10545-3
Breaking strength	≥3000 N	ISO 10545-4
Scratch hardness	9 Mohs	EN 101
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost	resistant- no alternation with 100 cycles	ISO 10545-12
Thermal shock resistance	resistant	ISO 10545-9
Crazing resistance	resistant	ISO 10545-11
Color shade variation	V2	CTDA
Coefficients of friction	Wet: DCOF: 0.70	ANSI/NFSI B101.3-2012

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

Tile Applications:			
Usage	Residential	Light Commercial	Commercial
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•



2x2 Basketweave  
set on 13x13 mesh sheet