

INNOVA



ECRU



12x24



20" Hexagon



20x20



13x13

FERRO



12x24



20" Hexagon



20x20



13x13

GRAPHITE



12x24



20" Hexagon



20x20



13x13

TAUPE



12x24



20" Hexagon



20x20



13x13


	VALUE	STANDARD
	Graphite PEI 4 Ecrú PEI 5 Taupe PEI 5 Ferro PEI 5	
Abrasion resistance		GLAZED ISO 10545-7
Water absorption	E ≤% 0.5	ISO 10545-3
Breaking strength	≥27 N/mm ² ≥35 N/mm ²	ISO 10545-4
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost	no alteration	ISO 10545-12
Thermal shock resistance	no alteration	ISO 10545-9
Color shade variation	V3	CTDA
Coefficients of friction	Dcot: 0.66	ISO 10545-17

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•



3x10



2x2 Mosaic



3x12 Floor Bullnose