

NOON



BURNET



8x48

8x48 plank available in Matte or Polished (chevron only available in matte)

HONEY



8x48

8x48 plank available in Matte or Polished (chevron only available in matte)



8x48 Chevron

EMBER



8x48

8x48 plank available in Matte or Polished (chevron only available in matte)

CHARCOAL



8x48

8x48 plank available in Matte or Polished (chevron only available in matte)

DAYLIGHT



8x48

8x48 plank available in Matte or Polished (chevron only available in matte)

	VALUE	STANDARD
Abrasion resistance	Daylight PEI 4 Ember PEI 4 Honey PEI 4 Burnet PEI 3 Charcoal PEI 3	GLAZED ISO 10545-7
Water absorption	0.04%	ISO 10545-3
Breaking strength	R 51,2 N/mm ²	ISO 10545-4
Scratch hardness	5 Mohs- Polished & Mohs- Natural	EN 101
Chemical resistance	UA, ULA, UHA- Natural GA, GLA- Polished	ISO 10545-13
Stain resistance	5	ISO 10545-14
Resistance to frost	resistant	ISO 10545-12
Thermal shock resistance	resistant	ISO 10545-9
Coefficients of friction	Wet: >0,60 Dry: >0,60	ASTM C1028
DIN Slipperiness	R 9	DIN51130

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•