

PATCHWALK



ANTRACITE



18x36



12x24



14x16
Hexagon



2x2 Mosaic

COTTO



18x36



12x24



14x16
Hexagon



2x2 Mosaic

BEIGE



18x36



12x24



14x16
Hexagon



2x2 Mosaic

FANGO



18x36



12x24



14x16
Hexagon



2x2 Mosaic

GRIGIO



18x36



12x24



14x16
Hexagon



2x2 Mosaic



3x12 Floor Bullnose

	VALUE	STANDARD
Abrasion resistance	PEI 5	ISO 10545-7
Water absorption	≤ 0.4%	ISO 10545-3
Breaking strength	40+55 N/mm ²	ISO 10545-4
Scratch hardness	8 Mohs	UNI 101
Chemical resistance	resists	ISO 10545-13
Stain resistance	complete	ISO 10545-14
Resistance to frost	frost proof	ISO 10545-12

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run. Prior to any installation, several loose tiles should be arranged and approved by the customer.

Tile Applications:	Residential	Light Commercial	Commercial
Usage	•	•	•
Floors	•	•	•
Walls	•	•	•
Countertops	•	•	•